

nextron



Circular Plastic 1P & 2P Series

Lightweight & Various Configuration Solution


Light-Weight


Error Proof
Several Key Codes & Color Codes Options


Push-Pull SnapLatch System


One Piece
Disposable Type

Features :

- Biocompatible materials compatible with various sterilization methods.
- Fool-proof: Several key codes & color codes options
- Various Insulator Configurations: Disposable, coaxial contact, fluidic or hybrid types



Type :

- Connector Type: Plug (Cable side), Receptacle (Panel & inline sides)
- Shell Size: 1P / 2P
- Terminal Type: Solder / Print Contact
- Pin Number Options: 2 to 34 Contacts
- Ingress Protection: IP50 / IP64 / IP67 (Mating)

Material	Electrical	Mechanical	Environmental
<ul style="list-style-type: none"> • Outer Shell & Back Nut: PSU/PEI • Contact: Copper alloy, Plating Au 	<ul style="list-style-type: none"> • Rated Current: 1.5A to 30A/Pin • Test Voltage (kV rms): 0.6 to 2.1 	<ul style="list-style-type: none"> • Durability: 1P > 2,000 cycles 2P > 1,000 cycles 	<ul style="list-style-type: none"> • Working Temperature: PSU: -50°C to +150°C PEI: -50°C to +170°C

nextron