



**Standard battery pack RRC2130 (2S1P)
with 7.6V / 3880mAh / 29.5Wh**

Features:

- Slim and flat standard battery pack with higher capacity and lower height than round cell packs with similar energy
- Allows to develop smaller and thinner portable devices with long runtime
- SMBus & SBDS Rev 1.1 compliant
- Fulfils JEITA standards, advanced temperature-dependent charging profile
 - Fastest charging
 - Maximized cycle life
- Impedance tracking and cell balancing
 - No manual recalibration necessary
 - Longest lifetime
- Comprehensive charging/discharging and passive safety systems
- Worldwide approvals
- Registered with recycling systems worldwide



Applications:

Suitable for use in slim devices for industrial and medical applications, etc.

Specification

General		Electrical Parameters	
Delivery status	30%	Nominal voltage	7.6V
battery capacity		Nominal capacity	3880mAh
Compliance information	CE / UN 38.3 / Gost / PSE / BSMI / TISI / RCM / EAC / CQC / UL2054 / KC / BIS / IEC 62133 / RoHS / FCC / REACH	Initial impedance	<200mΩ @ 1kHz at 20°C
Operating temperature	0°C to 45°C (charge) -20°C to 60°C (discharge)	Max. charge current	2700mA
Storage temperature	-20°C to 60°C max. -20°C to 25°C recommended	Max. charge voltage	8.7V
		Cont. discharge	3780mA
		Max. discharge	5670mA
		Life expectancy @25°C	>300 cycles with min. 85% of initial capacity
		1.9A Charge/0.75A Discharge	

Battery Dimensions		Safety Parameters PCM	
Length	150.6mm +/-0.5mm	Overcharge detection voltage	4390mV/cell
Width	86.2mm +/-0.4mm	Overcharge release voltage	4200mV/cell
Thickness	8.35mm +/-0.25	Overdischarge detection voltage	2750mV/cell
Weight	<172g	Overdischarge release voltage	3250mV/cell
Contacts	+,+,C,D,T,-,-	Overcharge detection current	3100mA
		Overdischarge detection current	6000mA

Recommended Accessories

Type	Product	Application
Standard Battery Charger	RRC-SMB-FPC	40W standard battery charger for optimized charging process with external power supply for worldwide use.
Battery Mating Connector	RRC-MC21-90-10 RRC-MC21-90-20	Mating Connector for standard smart batteries RRC2130, RRC2140. Available for 90° PCB mounting (top and edge).
Power Supply AC/DC	PS65	External power supply (worldwide use) for embedded battery charger RRC-PMM240 or for mobile devices. Included in RRC-SMB-UBC/MBC/FPC.
AC Power Cable	210950 for USA/CAN/JPN 210951 for EU/KOR 211333 for UK/SGP 211334 for AUS/NZL	Country specific power cable for PS65.
CAR Adapter DC/DC	RRC-SMB-CAR	90W car adapter with USB charging port. Power supplying in cars and trucks for RRC-SMB-UBC/MBC/FPC, RRC-PMM240 or mobile devices.

Germany/Headquarters

RRC power solutions GmbH
Technologiepark 1
D-66424 Homburg / Saar

Tel.: +49 6841 98090
Fax: +49 6841 9809280
Email: sales@rrc-ps.de
Web: www.rrc-ps.de

USA

RRC power solutions Inc.
18340 Yorba Linda Blvd.,
Suite 107-437
Yorba Linda, CA 92886-4104

Tel.: +1 714 777 3604
Fax: +1 714 777 3658
Email: usa@rrc-ps.com
Web: www.rrc-ps.com

Hong Kong

RRC power solutions Ltd.
S-V,6/F, Valiant Industrial Centre
2-12 Au Pui Wan Street
Fo Tan, N.T., Hong Kong

Tel.: +852 2376 0106
Fax: +852 2375 0107
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com

China

RRC power solutions Ltd.
Room 520, Yuanlin Building,
Aiguo Road No. 3066,
Luohu District,
Shenzhen 518021

Tel.: +86 755 8374 1908
Fax: +86 755 8374 1861
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com