






PCI Express[®] INTERCONNECT SOLUTIONS

PCIe[®] CEM AIC • PCIe[®] Capable Solutions • Future-Proof 56+ Gbps PAM4 Solutions

Samtec offers a number of solutions supporting the PCI Express[®] I/O interconnect bus. Samtec's PCI Express[®] product line includes connectors, cable assemblies and PCIe[®] CEM AICs that help drive fast, efficient, point-to-point communication.




PCI Express® CEM AIC Solutions

PCI Express® EDGE CARD SOCKETS & CABLE ASSEMBLIES


PAM4
56
Gbps

1.00 mm Pitch • x1 (36P), x4 (64P), x8 (98P), x16 (164P)

- PCIe® 3.0 Edge Card Connectors in vertical, right-angle and edge mount orientations (PCIE Series)
- PCIe® 4.0 Slim Edge Card Connector (PCIE-G4 Series)
- PCIe® 4.0 Low Profile Connector (PCIE-LP Series)
- PCIe® 5.0 Differential Pair Connector (PCIE-G5 Series)
- Also available: PCIe® 3.0 Jumper / Extension Cable Assemblies (PCIEC Series)



PCIE-LP & PCIE




8 mm Low Profile Design
vs.
11 mm Standard Height

PCI
EXPRESS®

8
Gbps


16
Gbps

32
Gbps



PCI Express® Jumpers for use as a Loop Back Extender, SerDes Physical Extender or as a physical extender for PCIe® card debug and analysis.

Right-Angle &
Edge Mount
Options




PCI Express® OVER FIBER CABLE ASSEMBLIES

8
Gbps

Optical FireFly™ Systems

- PCIe® 3.0 & 4.0 Optical Cable Assembly (PCUO Series)
 - x4, x8 and x16 PCIe® micro optical engines
- PCIe® 3.0 & 4.0 Adaptor Card with FireFly™ Optical Cable System (PCOA Series)
 - x16, x8, dual x8, x4, dual x4 and quad x4 configurations
 - PCIe® x16 Edge Card Connector



FIREFLY™

PCOA &
PCUO

Copper FireFly™ Systems

- PCIe® 3.0 & 4.0 Copper Cable System (PCUE Series)
 - 34 AWG ultra low skew twinax ribbon cable
 - x4 duplex system

PCI
EXPRESS®

8
Gbps

16
Gbps

32
Gbps

PCI-SIG®, PCI Express® and the PCIe® design marks are registered trademarks and/or service marks of PCI-SIG.

PCI Express® Capable Solutions

HIGH-SPEED EDGE CARD SOCKETS


PAM.4
56
Gbps

Choice of Pitches • Rugged Contact Systems

- PCIe® 4.0 Capable Mini Edge Card Connectors
 - 0.50 mm (.0197") Pitch
 - Right-angle (MEC5-RA Series) & vertical (MEC5-DV Series)
- PCIe® 3.0 & 4.0 Capable High-Speed Card Connectors
 - High-Speed Edge Rate® contacts on 0.80 mm pitch
 - Vertical, edge mount and right-angle orientations (HSEC8 Series)
 - PCIe® 4.0 & 5.0 Capable Differential Pair Socket (HSEC8-DP Series)
- PCIe® 3.0 & 4.0 Capable High-Speed Edge Card Connector
 - Edge Rate® contact system on 1.00 mm pitch
 - Vertical orientation (HSEC1-DV Series)
 - PCIe® 5.0 Capable Differential Pair Connector in development (HSEC1-DP)

EDGE
RATE
CONTACT

HSEC8-DV &
HSEC1-DV



HIGH-SPEED MEZZANINE CONNECTORS & CABLE ASSEMBLIES

28
Gbps

Choice of Pitches • Integral Power / Ground Plane

- 0.50 mm & 0.80 mm pitch Q Strip® Ground Plane Connector Strips & Cable Assemblies
- 0.635 mm pitch Q2™ Rugged Differential Pair Ground Plane Header & Cable Assemblies
- 0.80 mm pitch Q Rate® Rugged, Slim Body Connector Strips & Cable Assemblies
- Visit samtec.com/QSeries for details

QSERIES®

EQRD / QRF8

HQCD / QTH



RUGGED HIGH-SPEED CONNECTORS & CABLE ASSEMBLIES

PAM.4
56
Gbps

Rugged Edge Rate® Contact System • 0.80 mm Pitch

- High-Speed Connector Strips (ERM8/ERF8 Series)
- Edge Card Twinax Cable Assembly (ECDP Series)
- Micro Coax & Twinax High-Speed Cable Assemblies (ERCD/ERDP Series)

EDGE
RATE
CONTACT

ERDP / ERF8



HIGH-SPEED / HIGH-DENSITY ARRAYS

PAM.4
56
Gbps

Routing & Grounding Flexibility • Rugged Contact Systems

- SEARAY™ 0.50" pitch Open-Pin-Field Arrays (SEAM/SEAF Series)
- SEARAY™ 0.50" pitch Cable Assembly (SEAC Series)
- DP Array® .085" X .100" Differential Pair Array (DPAM/DPAF Series)

SEARAY™

SEAC / SEAM



Future-Proof 56+ Gbps PAM4 Solutions

In addition to products designed to support the latest PCIe® data rates, Samtec has a full line of ultra high-performance solutions engineered for 56 - 112 Gbps PAM4 speeds and beyond, providing future-proof design flexibility for the support of next generation PCI Express® technologies.


NEXT GEN HIGH-SPEED EDGE CARD SOCKETS

PAM4 56 Gbps PAM4 112 Gbps

0.80 mm Pitch Edge Rate® Differential Pair Connector

- Up to 56 Gbps PAM4 performance
- PCIe® 4.0 & 5.0 Capable (HSEC8-DP Series)


EDGE RATE CONTACT



HSEC8-DP

0.60 mm Pitch Edge Rate® Differential Pair Connector

- Up to 56 Gbps PAM4 performance
- PCIe® 4.0 & 5.0 Capable (HSEC6-DV Series)
- Compliant to SFF-TA-1002: x4 (IC), x8 (2C), x16 (4C & 4C+)
- In Development: 0.60 mm pitch High-Speed Cable Assembly & Extreme Performance 112 Gbps PAM4 Connector



HSEC6-DV

EXTREME PERFORMANCE / DENSITY ARRAYS

PAM4 56 Gbps PAM4 112 Gbps

NovaRay® Extreme Density & Performance Arrays

- 4.0 Tbps aggregate data rate - 9 IEEE 400G channels
- Mating 0.80 mm pitch socket cable assembly
- In Development: future-proof NovaRay® I/O Extreme Density Bulkhead Cable System




NVAM/ NVAF

AcceRate® HP High-Performance Open-Pin-Field Arrays

- 0.635 mm Pitch, four row design with up to 400 total pins; roadmap to 1,000+ pins
- Data rate capable with PCIe® 5.0 and 100 GbE
- In Development: mating cable assembly

ADM6/ ADF6



Extreme Density Designs in Development

AcceRate® HD Ultra-Dense Open-Pin-Field Arrays

- 0.635 mm pitch Edge Rate® contacts; up to 400 I/Os
- Open-pin-field design for grounding and routing flexibility
- In Development: right-angle and additional stack heights

APM6/APF6

DIRECT CONNECT CABLE TO IC PACKAGE TECHNOLOGY

PAM4 56 Gbps PAM4 112 Gbps

Si-Fly™ Ultra-High Density Direct Connect to IC Package System

- In Development: Si-Fly™ technology eludes the BGA, routing signals directly from the silicon package through a long-reach cable
- Extreme channel performance enabling 25.6 TB aggregate with a path to 51.2 TB
- Visit samtec.com/si-fly for details

