



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14												
COM	COM	E1	D1	C1	DP1	E2	D2	C2	DP3	E4	D4	C4	DP4	E5	D5	C5	DP5	E6	D6	C6	B6	A6	F6	G6		
PIN	15	16	17	18	19	20	21	22	23	24	25	26	27	28												
COM	C2	C4	F3	D3	C3	DP3	F4	D4	C4	DP4	E5	D5	C5	DP5	E6	D6	C6	B6	A6	F6	G6					
PIN	29	30	31	32	33	34	35	36	37	38	39	40	41	42												
COM	D4	C4	DP4	E5	D5	C5	DP5	E6	D6	C6	B6	A6	F6	G6												
PIN	43	44	45	46	47	48	49	50	51	52	53	54	55	56												
COM	E6	D6	C6	B6	A6	F6	G6	B5	A5	F5	D5	C5	DP5	E6	D6	C6	B6	A6	F6	G6						
PIN	57	58	59	60	61	62	63	64	65	66	67	68	69	70												
COM	B5	A5	F5	D5	C5	DP5	E6	D6	C6	B6	A6	F6	G6	B5	A5	F5	D5	C5	DP5	E6	D6	C6	B6	A6	F6	G6
PIN	71	72	73	74	75	76	77	78	79	80	81	82	83	84												
COM	F4	G4	B3	A3	F3	G3	COL1	F4	G4	B3	A3	F3	G3	COL1												
PIN	85	86	87	88	89	90	91	92	93	94	95	96	97	98												
COM	B2	A2	F2	G2	B1	A1	F1	B2	A2	F2	G2	B1	A1	F1												
PIN	99	100																								
COM	G1																									

NOTE:

1. DISPLAY TYPE: NEGATIVE, TRANSMISSIVE, BLUE
2. VIEWING DIR.: 6:00
3. DRIVE METHOD: STATIC, Vop5V
4. OP. TEMP.: -40°C~80°C
5. ST. TEMP.: -40°C~90°C
6. U.V. FILTER POLARIZER

修改日期	内 容	河北冀雅电子有限公司	
1	04.07	CHANGE SIZE	型号 JT1-99537
2	2.9.3	ADD PIN CAMBER	日期 99.11.16
3	3.6.9	CHANGE POL. AC.	制图 李 锦 堂
4			日期 99.11.16
5			审核
6			批准
			页数 1/1
			编号尺寸 X:0.1Y:0.1